


10018405

ContiTech SCHWINGMETALL®-Puffer A

Form 31658/A Qualität NR 40° Sh d= 20mm x h= 25mm, Gew. M6 x 19mm



Technical Data

Weight	0,022 kg per piece
SM-type	A
diameter	20,0 millimeter
sm-height	25,0 millimeter
grade shore	40A
type of thread	M6
length of thread	19,0 millimeter
number of mold	31658/A
Сх	5,0
Су	5,0
Cz	27,0
eCl@ss 6.2	23-18-90-90
Fx	60,0 Newton
Fy	60,0 Newton
Fz	150,0 Newton
Conformity	
Commodity code	40169991

Page 1 of 2

白

Anton Klocke Antriebstechnik GmbH Senner Straße 151 | D-33659 Bielefeld

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott | Amtsgericht Bielefeld | HRB 34306 Fon +49 (0)521 95005 - 01| Fax +49 (0)521 95005 - 11 | info@klocke-antrieb.de | www.klocke-antrieb.de



10018405

ContiTech SCHWINGMETALL®-Puffer A

Form 31658/A Qualität NR 40° Sh d= 20mm x h= 25mm, Gew. M6 x 19mm

Conformity	
Dual-Use	no
REACH regulation	2006/1907/EG (REACH)
RoHS directive	2011/65/EU (RoHS II)
RoHS directive (III)	2015/863/EC (RoHS III)

* n/s - not specified

n/a - not applicable

** technical specifications/ conformities

This data sheet has been created with great care and all information has been checked for correctness. However, no liability is accepted for any incorrect or incomplete information. Product images and drawings are for illustration purposes only and may vary in detail. Due to the constant further development of the products, changes in the product range and the product design are reserved! Performance and consumption data as well as descriptions may therefore differ. The use of the products is beyond our control and is therefore not our area of responsibility.

