

10264659

ContiTech® Zweifaltenbalg

FD 120-17 VP

19.12.2022 12:16:16

| Technical | Data | |
|-----------|------|--|
| | | |

| Weight | 0,100 g per piece |
|---------------------------------|-----------------------------|
| Special design | VP - bellow only |
| Number of bellows | Two bellows |
| cylinder stroke | 130,00 millimeter |
| Screw-in thread | without |
| Ausführung Balgzylinder | D - demountable connections |
| Connection variant air actuator | without |
| diameter | 215,0 millimeter |
| eCl@ss 6.2 | 27-29-05-90 |
| Installation height | 75,00 millimeter |
| Conformity | |
| Commodity code | |
| China-RoHS | n/a |
| Dual-Use | no |
| REACH regulation | 2006/1907/EG (REACH) |
| RoHS directive | 2011/65/EU (RoHS II) |
| RoHS directive (III) | 2015/863/EC (RoHS III) |
| | |

Page 1 of 2

Anton Klocke Antriebstechnik GmbH Senner Straße 151 | D-33659 Bielefeld

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott | Amtsgericht Bielefeld | HRB 34306 Fon +49 (0)521 95005 - 01| Fax +49 (0)521 95005 - 11 | info@klocke-antrieb.de | www.klocke-antrieb.de



10264659

ContiTech® Zweifaltenbalg

FD 120-17 VP

* n/s - not specified n/a - not applicable

** technical specifications/ conformities

This data sheet has been created with great care and all information has been checked for correctness. However, no liability is accepted for any incorrect or incomplete information. Product images and drawings are for illustration purposes only and may vary in detail. Due to the constant further development of the products, changes in the product range and the product design are reserved! Performance and consumption data as well as descriptions may therefore differ. The use of the products is beyond our control and is therefore not our area of responsibility.

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott | Amtsgericht Bielefeld | HRB 34306 Fon +49 (0)521 95005 - 01| Fax +49 (0)521 95005 - 11 | info@klocke-antrieb.de | www.klocke-antrieb.de