

10264670

ContiTech® Zweifaltenbalg

FD 138-18 VP ECO

19.12.2022 12:17:07

Technical Data	
----------------	--

Weight	0,100 g per piece
Special design	VP - bellow only
Number of bellows	Two bellows
cylinder stroke	145,00 millimeter
Screw-in thread	without
Ausführung Balgzylinder	D - demountable connections
Connection variant air actuator	without
diameter	230,0 millimeter
eCl@ss 6.2	27-29-05-90
Installation height	75,00 millimeter
Conformity	
Commodity code	
China-RoHS	n/a
Dual-Use	no
REACH regulation	2006/1907/EG (REACH)
RoHS directive	2011/65/EU (RoHS II)
RoHS directive (III)	2015/863/EC (RoHS III)

Anton Klocke Antriebstechnik GmbH Senner Straße 151 | D-33659 Bielefeld

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott / Amtsgericht Bielefeld / HRB 34306 Fon +49 (0)521 95005 - 01 / Fax +49 (0)521 95005 - 11 / info@klocke-antrieb.de / www.klocke-antrieb.de



10264670

ContiTech® Zweifaltenbalg

FD 138-18 VP ECO

* n/s - not specified n/a - not applicable

** technical specifications/ conformities

This data sheet has been created with great care and all information has been checked for correctness. However, no liability is accepted for any incorrect or incomplete information. Product images and drawings are for illustration purposes only and may vary in detail. Due to the constant further development of the products, changes in the product range and the product design are reserved! Performance and consumption data as well as descriptions may therefore differ. The use of the products is beyond our control and is therefore not our area of responsibility.

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott | Amtsgericht Bielefeld | HRB 34306 Fon +49 (0)521 95005 - 01 | Fax +49 (0)521 95005 - 11 | info@klocke-antrieb.de | www.klocke-antrieb.de