
Klocke

10062257

BRECOFLEX® - Zahnriemen

32 T20/5300 mm, PAZ



Technical Data		0
Weight	1,251 kg per piece	
belt type	standard	
eCl@ss 6.2	23-17-02-05	
is standard	yes	
material type	TPUST1	
pitch length	5.300,00 millimeter	
polyamide tissue	PAZ	
tension member belt	standard	
tooth profile	T 20	
width	32,00 millimeter	
Conformity		
Commodity code	39269097	
China-RoHS	n/a	
Dual-Use	no	
REACH regulation	2006/1907/EG (REACH)	
RoHS directive	2011/65/EU (RoHS II)	
RoHS directive (III)	2015/863/EC (RoHS III)	

말하게 문

高

Anton Klocke Antriebstechnik GmbH Senner Straße 151 | D-33659 Bielefeld


Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott / Amtsgericht Bielefeld / HRB 34306 Fon +49 (0)521 95005 - 01 / Fax +49 (0)521 95005 - 11 / info@klocke-antrieb.de / www.klocke-antrieb.de



10062257

BRECOFLEX® - Zahnriemen

32 T20/5300 mm, PAZ



* n/s - not specified n/a - not applicable

** technical specifications/ conformities

This data sheet has been created with great care and all information has been checked for correctness. However, no liability is accepted for any incorrect or incomplete information. Product images and drawings are for illustration purposes only and may vary in detail. Due to the constant further development of the products, changes in the product range and the product design are reserved! Performance and consumption data as well as descriptions may therefore differ. The use of the products is beyond our control and is therefore not our area of responsibility.

Anton Klocke Antriebstechnik GmbH Senner Straße 151 | D-33659 Bielefeld

Geschäftsführer Dipl.-Ing. (FH) Thorsten Kott | Amtsgericht Bielefeld | HRB 34306 Fon +49 (0)521 95005 - 01| Fax +49 (0)521 95005 - 11 | info@klocke-antrieb.de | www.klocke-antrieb.de